KERN RPB30K5DM

Retail scale with memories for item prices



Mains adapter external



Measuring system	
Adjustment options:	External calibration
Linearity:	15 g 30 g
Number of weighing ranges:	2
Readability [d]:	5 g 10 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5 g 10 g
Resolution:	3 3.000
Resolution (non verifiable):	6000
Resolution (verifiable):	6000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-29,990 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	15 kg 30 kg
Weighing system:	Strain gauge
Weighing units:	g kg

Display	
Additional Display possible:	no
Display digit height:	1,500 cm

Technical data about verification		
Minimum load [Min]:	100 g	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	5 g 10 g	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	CH EURO UK US

Power supply	
Operating time (Backlight off):	60 h
Operating time (Backlight on):	30 h
Rechargeable battery:	Rchrg. battery optional

n/a:

Service


Adjustment at the location of installation: 961-248		
DAkkS Certificate:	963-128	
Verification:	965-228	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Price computing scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	365 x 335 x 190 mm
Gross weight:	3,500 kg
Net weight:	2,800 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	313 x 263 x 108 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	313 x 263 x 108 mm
Revolving screw feet:	yes
Weighing surface (WxD):	204 x 263 mm

KERN RPB30K5DM





Piktogramme

STANDARD















OPTION





FACTORY

